

Available in **5 sizes** for a variety of installations

- 1 Promotes excellent air circulation with PSC energy efficient thermally protected motors
- 2 Integrated exterior shutters that open and close automatically
- 3 Quickly remove any unwanted odors and humidity
- 4 Balanced 4-blade fan assembly totally enclosed for protection & OSHA compliance
- 5 Housing constructed of durable 20-gauge galvanized steel that won't rust



| MODEL | BLADE DIAMETER | ROUGH-IN OPENING      | CFM  | AMPS |
|-------|----------------|-----------------------|------|------|
| IF14  | 14 in.         | 17.25 in. x 17.25 in. | 1400 | 2.65 |
| IF18  | 18 in.         | 20.75 in. x 20.75 in. | 3000 | 5.34 |
| IF24  | 24 in.         | 28.25 in. x 28.25 in. | 4100 | 4.35 |
| IF30  | 30 in.         | 34.25 in. x 34.25 in. | 5500 | 6.30 |
| IF36  | 36 in.         | 40.25 in. x 40.25 in. | 9000 | 5.15 |

PERFECT FOR:



AGRICULTURE



AUTOMOTIVE



INDUSTRIAL



LIVESTOCK



1-SPEED  
OPERATION



ENERGY EFFICIENT  
COMPONENTS



WIRING  
REQUIRED